

INDEX

2d & 3d oxidation 78
(100) and (111) orientation 35
{311} defects 139, 143, 144
+1 model 139

A

AC sputter deposition (RF sputter deposition) 172
accelerator (ion implantation) 125
activation (electrical activation) 10, 97, 140
aerial image 201, 207, 218
ALD (atomic layer deposition) 164
alignment 213
analyzer (ion implantation) 124
anomalous diffusion 142, 144
antenna effect 270
antenna ratio 270
APCVD (atmospheric pressure cvd) 148
APF (advanced patterning film) 244
area defects 42
arrival angle distribution 176
ashing 6
att-PSM (attenuated phase shift mask) 233, 235

B

BARC (bottom anti reflective coat) 293
barrel etcher 261
BCC (body centered cubic) 33
BEOL (back end of the line) 276
bias sputtering 177
bird's beak 5, 65
Boltzmann approximation 116
Bragg reflector ($\lambda/4$ Bragg reflector) 250
Bravais lattice 32
bridging oxygen 62
BTS (bias temperature stress) 88
Burgers vector 40

C

CAR (chemically amplified resist) 206
channeling 131
charge defects 79
charged interstitial / vacancy 38
chemical etching 257
chop mask (cut mask) 246
clam shell defects 137, 138

CMOS process flow 3
CMP (chemical mechanical polishing / planarization) 7
coherence 217
collimated sputtering 177
complementary error function (error function) 103
conformality 13, 146, 169
contact printing (see also nano imprint lithography at page 251) 193, 194
contacts 276, 281
contacts formation 28
contrast (aerial intensity) 230
contrast (resist contrast) 208
copper process flow 291
cut mask (chop mask) 246
CV characterization of Si 81
CVD (chemical vapor deposition) 147, 148
Czochralski (cz) technique 45

D

damascene 291
DC sputter deposition 171, 174
Deal and Grove model 66
deep depletion 86
deep donor / acceptor 38
defects 36
dehydration bake 209
denuded zone 43
developer 188
diamond structure 34
dielectrics BEOL 276, 287
diffusion controlled regime 70
diffusion rate (oxide) 70
dislocations 40
DoF (depth of focus) 230, 231
dopant diffusion 96
double patterning 241
DQN (dq= diazoquinone, n = novolac) 203
dry etching (plasma etching) 255, 256
DSA (directed self assembly) 252

E

EBDW (electron beam direct writing) 249
edge dislocation 40, 53
Einstein relationship 117
electrical activation (activation) 10, 97, 140
electrical solubility 97
electromigration 285, 297
electromigration analytical model 302
electromigration qualitative model 300

EGS (electronic grade silicon) 44
electronic stopping power 132, 134
ellipsometer 95
emitter push 112
end point detection 264, 265
enhanced diffusivity 106
EOR defects (end of range defects) 133, 138
error function (complementary error function) 103
etching 253
EUV / EUVL (extreme UV lithography) 250
evaporation (pvd evaporation) 165
excimer 191
extractor (ion implantation) 123
extrinsic stacking fault 42

F

far field approximation (Fraunhofer approximation) 221
FCC (face centered cubic) 33
FEOL (front end of the line) 25
Fick's laws 98
final bake (or hard bake) 211
fixed oxide charge 79, 87
Fraunhofer approximation (far field approximation) 221
Frenkel pair 36
FSG (fluorine-doped silicon gas) 291
fused silica 62

G

g-line / i-line / h-line 190
g-line / i-line photoresist positive process 204
gate stack formation 16
gettering 42, 43
growth rate (oxide) 70

H

h-line / g-line / i-line 190
halide species 256
hard bake (or final bake) 211
HDMS (hexamethyldisilane) 209
HDPCVD (high density plasma cvd) 162
Henry's law 68
high density plasma systems (ion milling) 263
hillocks 285
Huygens-Fresnel principle 221
hydrogen anneal 30, 287
hydroxyls 63

I

- i-line / g-line / h-line 190
- imbalanced pattern 247
- immersion lithography 239
- inactive resin 203
- inhibitor 260
- interface trapped charge 79, 87
- intermediate / global interconnects 276, 284
- interstitials 36
- intrinsic point defects 36
- intrinsic stacking fault 42
- ion enhanced etching 259
- ion enhanced etching model 274, 275
- ion enhanced inhibitor etching 260
- ion milling (high density plasma systems) 263
- ion trajectory distortion due to resist charging 269
- ionized sputtering 185

K

- kurtosis 130

L

- latent image 201
- LDD (lightly doped drain) 19
- lens pupil function 223
- light contrast (aerial intensity contrast) 230
- line defects 40
- lithography 188
- loading effect 268
- local interconnects 276, 278
- LOCOS (LOCAl Oxidation of Silicon) 4, 65
- LPCVD (low pressure cvd) 157, 183

M

- magnetron sputtering 177
- mass action law 117, 118
- Massoud model 73
- maximum pull rate / speed 46, 56, 57, 58
- metallic contaminant removal 11
- MGS (metallurgical grade silicon) 44
- micro trenching 269
- micro-loading effect 268
- milller indexes 34

miller planes 34
mobile ionic charges 80
MTTF (median time to failure) 298, 299

N

NA (numerical aperture) 51, 216
nano imprint lithography 251
network formers (substitutional impurities) 63
network modifiers (interstitial impurities) 63
nitridation 89
non bridging oxygen 62
non conformality 13, 146, 169
nuclear stopping power 132, 133

O

OAI (off axis illumination) 233, 234
objective lens 222
OPC (optical proximity corrections) 233, 236
optical emission spectroscopy 264
overlay 21, 213
oxidation 61, 64
oxidation enhanced (/ retarded) diffusion 110
oxide trapped charges 80

P

PAC (photo active compound) 203
pad mask (patch mask) 246
PAG (photo acid generator) 206
parallel plate etcher 262
passivation layer 260
patch mask (pad mask) 246
PEB (pre exposure bake, or soft bake) 206, 210, 211
PECVD (plasma enhanced cvd) 14, 158, 184
photo masks 191
photoresist 188, 203, 205
photoresist application (resist application) 210
photoresist development 202
physical etching (sputtering) 258
pile up 77, 108
plasma damage 270
plasma etching (dry etching) 255, 256
plasma oxidation 93
PMD (pre metal dielectric) 291
point defects 36
point defects concentration 54,55
point source deposition rate 166

- polygranular cluster 300
- polysilicon 16
- precipitates 43
- projected range 127
- projection printing 193, 197, 199
- proximity printing 193, 195
- PDM (phase shift mask) 233, 235
- pull rate / speed (see also maximum pull rate) 46, 56, 57, 58
- PVD (physical vapor deposition) 147
- PVD evaporation 165
- PVD sputtering 170

Q

- QBD (charge-to-breakdown) 89

R

- radiation damage 270
- radical oxidation 92
- Rayleigh criterion 231
- reaction controlled regime 70
- reaction rate (oxide) 70
- reactive sputter deposition 177
- reduction reticles 191
- registration 21, 213
- resist application (photoresist application) 210
- resist contrast 208
- resist resputtering 269
- resolution 51
- resolution limit 195
- resolution limit of coherent imaging 224, 227
- resolution limit of partially coherent imaging 228, 229
- RET (resolution enhancement techniques) 233
- reverse annealing 140
- reverse micro-loading effect 268
- reverse short channel effect 144
- RF sputter deposition (AC sputter deposition) 172
- RIE (reactive ion etching) 262
- RTO (rapid thermal oxidation) 91
- RTP (rapid thermal processing) 89, 92

S

- SADP (self aligned double patterning) 242
- SALICIDE (Self Aligned siLICIDE) 27, 279
- scalloped edges 293, 296
- scanner 199, 200, 210
- Schottky diode 18, 281

screw dislocation 53, 54
scribe lines 21, 200
segregation 108
segregation coefficient 47, 59, 60, 76
selectivity 253
SEM (scanning electron microscope) 51, 52
sheaths 159, 160
short channel effect 18
shunt 286
silicide 26, 278
silicon oxidation equipments 90
SIMS (secondary ion mass spectrometry) 114
skewness 130
slurry 7
small planar source deposition rate 167
SOD (spin on dielectric) 15
soft bake (or pre exposure bake) 210
SOG (spin on glass) 15
solid solubility 43, 97
solvent 203
SPA (slot plane antenna) 93
spacers formation 22
spanning grain 300
SPE (solid phase epitaxy) 136
sputter deposition (pvd sputtering) 26, 170
sputtering (physical etching) 258
sputtering yield 175
SRAF (sub resolution assist features) 237
SSRM (scanning spreading resistance microscopy) 115
stacking faults 42
stagnant layer 66, 152
stepper 199, 200, 210
STI (shallow trench isolation) 6
sticking coefficient 169
stopping power 128
straggle (standard deviation) 127, 130
supersaturation 111, 143, 144

T

τ (time delay) 289
tddb (time dependent dielectric breakdown) 88
TED (transient enhanced diffusion) 141, 142, 143, 144
TEM (transmission electron microscope) 51, 52
thermal budget 12
thermal reflow 212
thermoionic emission current 282
throughput 192
time delay (τ) 289
TMAH (tetra methyl ammonium hydroxide) 211
transmission function 221

tungsten plugs (W plugs) 283
tunneling regime 282

U

UFU (undoped fluorine undoped) 291

V

vacancies 36
vias 276
voids 285
volume defects 43

W

W plugs (tungsten plugs) 283
wet etching 254
Wolff rearrangement 204

Y

yield (sputtering yield) 175